




**Up to 5 year warranty**

European quality - Danish design. 2200i comes with a 2 year warranty. Three extra year of warranty for free requires online product registration on [protectglobal.com/extra-warranty](http://protectglobal.com/extra-warranty)



**Possibility of 4 angled nozzles**

2200i comes with a straight nozzle. However it can easily be exchanged with different angled nozzles with one or three holes straight or 30°.



**XTRA+ fog fluid**

Sturdy, reusable fluid container with XTRA+ fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.



**Tests & approvals**

The model 2200i is tested and approved in accordance with IEC 62642-8 (a worldwide standard for fog cannon units). Test certificates can be obtained on [protectglobal.com](http://protectglobal.com) (documentation).

# 2200i™

Model 2200i is the most powerful fog cannon for anti-burglary protection. It has an enormous capacity and discharges with a massive roar. 2200i is designed for warehouses, large shops, shopping centers and buildings with mezzanines and large entrance ways.



**Features:**

- Discharges 2700 m<sup>3</sup> of fog at full speed in 60 seconds
- Flexible adjustment between 900 and 2875 m<sup>3</sup> to exactly fit the size of the room
- 100 % silent in standby mode
- Pulse function for up to 10 min. (effective maintenance of the fog)
- Compatible with any alarm system including ZOLO GSM Alarm System
- Compatible with IPCard, MultiCard and IntelliBox
- Data log memory possible with IntelliSuite
- Built-in daily, automatic battery test
- Integration with all types of alarm systems
- 100 % silent in standby mode
- Prepared for 4 different angled nozzles and nozzle extension piece

**Specifications:**

Fog performance, examples: 60 sec. + 10 min. pulse: 3700 m <sup>3</sup>
3 time settings from 900-2875 m <sup>3</sup>
Optional pulse function (can shoot several times)
3 l. reusable fluid container included
Enough fluid for 5 discharges in one container
Electronic fluid measurement
Power consumption: 1680 W
Mains connection: 230V, 50 Hz
Standby consumption after heating up: 80 W (on average)
Standby consumption when heat is disabled: 5-10 W
Heating time from cold: 30 min.
Re-heating time after fog discharge: 0-14 min.
Operating temperature (min./max.): 5/80° C.
Input: 5 signals
Output: 3 signals
On/off dipswitches for setting of fog time, signals and heating
Backup of electronics and pump (2 x 12V, 1.2 Ah)
Power backup after power failure: Up to 3 hours
Built-in automatic battery testing
Optical, audible and electrical signals/indicators
Status indicator on PCB
External status indicator
Anti-sabotage, impact-resistant steel casing
Colours available: White and black
Dimensions: L: 633, W: 352, H: 172 mm
Installation weight: 24,8 kg

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS